

ASPHALT PATCH MASTER™

Hot Mix Asphalt On Demand Portable Unit



Available in LP or Diesel Powered Units Models

The Asphalt Patch Master™ (APM) is a self-contained portable unit for producing true modified hot mix asphalt for Pothole Patching in all-weather applications.

With the APM, you can now make a durable, long-lasting rubberized patch.



The APM is designed to be used with PelletPATCH and PelletRAP materials directly at the repair site in just the quantity you need.

The APM is mounted on a Trailer and produces up to 400 lbs of hot mix in less than 15 minutes.

- ◆ Eliminates lost labor and production time traveling to an asphalt plant
- ◆ Minimizes wasted material by heating sufficient pellets for the size of the hole
- ◆ Application of a rubberized patch that is permanent and durable
- ◆ Environmentally friendly; made from recycled waste tires



PelletPATCH Distributors, LLC
smarra@PelletPATCH.com
201-374-2500
Cell 201-304-1798

www.PelletPATCH.com



ASPHALT PATCH MASTER™

Technical Specifications

LP Powered APM trailer package includes:

- ◆ 10 Foot x77" Appalachian Trailer with Brake Setup
- ◆ 2 inch ball connector
- ◆ 15 inch radial tires
- ◆ 5,000lb capacity
- ◆ Mounting of APM unit
- ◆ 2—LP Tanks with Tank Holders (plumbing, tank cover & locks)
- ◆ Spare tire
- ◆ 100% Hydraulic
- ◆ LED Lighting
- ◆ Fold Down Rear Gate and ramp
- ◆ Diamond plate Tool Box (60"x24"x18")
- ◆ Wheelbarrow & Safety Cone Rack
- ◆ Scraper & Broom
- ◆ Rake & Shovel

Diesel Powered APM trailer package includes:

- ◆ 10 Foot x77" Appalachian Trailer with Brake Setup
- ◆ 2 inch ball connector
- ◆ 15 inch radial tires
- ◆ 5,000lb capacity
- ◆ Mounting of APM unit
- ◆ 45 Gal. diesel fuel tank w/locking cap & 10 micron filter system
- ◆ Spare tire
- ◆ 100% Hydraulic
- ◆ LED Lighting
- ◆ Fold Down Rear Gate and ramp
- ◆ Diamond plate Tool Box (60"x24"x18")
- ◆ Wheelbarrow & Safety Cone Rack
- ◆ Scraper & Broom
- ◆ Rake & Shovel
- ◆ 5lb Fire Extinguisher—Mounted



Hot Mix Asphalt On Demand

smarra@PelletPATCH.com

201-374-2500
Cell 201-304-1798

www.PelletPATCH.com



ASPHALT PATCH MASTER™

General Specifications

385# Batch capacity

10 – 15 Minute batch cycle time

3/16 in. Carbon steel mix drum with insulated jacket paneling on (4) sides

Hydraulic motor driven agitator with chain and sprocket reduction

(4) Mix blades

(2) Drum scraper blades

Hydraulic mix drum dump system

Hydraulic lid lift system

770 mbtu/hr. Beckett oil burner (Diesel Fuel Only) operating at 350mbtu/hr.

(2.5 gph nozzle)

Beckett 7556 GeniSys Burner Control system.

On / off manual control

Flame out protection with prestart purge time delay

Drum position / burner interlock safety system

Kubota OC series single cylinder air cooled diesel engine

Tier 4 Environmental rating

Electric Start

Compression release system

Electric fuel pump

40 Amp output alternator



Hot Mix Asphalt On Demand

smarra@PelletPATCH.com

201-374-2500

Cell 201-304-1798

www.PelletPATCH.com



FOR FURTHER INFORMATION CONTACT



PelletPATCH Distributors LLC

smarra@PelletPATCH.com

201-374-2500

Cell 201-304-1798

www.PelletPATCH.com